

Bloc Tanks



FUEL COMPATIBILITY KEY



FES BLOC Tanks are the best solution for the storage and dispensing of diesel, petrol and lubricant oils. They offer a flexible solution to storing combustible liquid as well as improving fuel dispensing and management solutions. A practical design ensures a fast, easy and convenient installation in any location, indoors or outdoors.

BLOC TANKS OFFER A FAST, EASY AND CONVENIENT FUEL STORAGE SOLUTION

Mobile and modular units ensure fast and easy transportation options to site. Easily relocatable.

Minimal site works and preparation required. A place, fill and pump installation process offering versatility and speed on commissioning.

Free standing design allows for 360° tank viewing and inspection.

High-grade paint finish ensures longer durability in the elements.

DOUBLE-WALL CONTAINMENT FOR ADDED SECURITY

Self-bunded tanks are ASI692 and ASI940 designed as integral secondary containment and therefore do not require independent bunds for leak containment.

110% bunded tank = 100% Primary Tank + 10% interstitial space.

STANDARD FEATURES

- Meets ASI692 and ASI940 Australian Standards.
- Bunded tank construction consists of a 5mm primary steel tank and a 3mm secondary steel tank.
- Baffled internally to reduce product movement should the unit be moved with contents.*
- Accessible and removable tank manway for internal tank maintenance and cleaning.
- Recessed spill box area under lockable lid to secure transfer pump.
- Sectional cut-outs on sides of spill box to allow flexible hoses or pipework to external requirements (i.e. generators).
- Curved roof feature for water drainage to top of tank.*
- Complete with aluminium gauged dipsticks, 1 x galvanized updraft vent breather system and multiple port fittings.
- Air tested and hydro tested prior to leaving our factory.
- Mobile and modular design allows for ease of transportation.
- 300-350 micron thickness 'WHITE' paint finish as standard. Other colour options are available upon request.
- Flammable and combustible liquid safety labels and decals supplied as standard.
- Fork lift pockets and certified tie down/lifting points at each corner.

Custom colours, coatings, dimensions and refuelling equipment packages are available upon request.

*Conditions apply. Some features standard, some optional extras. Depends on product range

Bloc Tanks



INSIDE LID

- 1 x 2" Dip / Fill Point
- 2 x 2" Suction Ports
- 2 x 2" Return Ports
- 2 x 1" Suction Ports
- 2 x 1" Return Ports

EXTERIOR OF TANK

- 1 x 2" Emergency Vent
- 1 x 2" Interstitial Dip
- 1 x 2" Suction Port
- 1 x 1" Return Port
- 1 x 4" Submersible Pump Provision
- 1 x 6" Submersible Pump Provision
- 1 x 2" Free Vent Port

MOBILE AND MODULAR

- Fork lift pockets and certified tie down/lifting points at each corner.
- Larger BLOC tanks incorporate skid tray base for tilt tray loading.
- Tanks can be stacked three high empty.

FES BLOC TANK SPECIFICATIONS

MODEL	CAPACITY	SFL	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	WEIGHT (kg)	BAFFLED
FES BLOC 1000L	1,250L	1,000L	1,874	1,100	1,254	758	NO
FES BLOC 2500L	2,755L	2,500L	2,274	1,674	1,254	1,189	YES
FES BLOC 4500L	4,785L	4,500L	2,774	2,274	1,254	1,678	YES
FES BLOC 6000L	6,180L	6,000L	3,574	2,274	1,254	2,036	YES
FES BLOC 10000L	11,500L	10,000L	6,058	2,438	1,295	4,443	YES

Dimensions are nominal only. Alternative capacities available upon request.

The storage of flammable liquids can be accommodated with the relevant venting and accessory change. Remember to check with local authorities.



YOUR LOCAL DISTRIBUTOR

Genset Hire and Sales Australia

28 Felspar Street, Welshpool, WA 6106

E sales@ghasa.com.au

T +61 08 9359 1988